



Introduction

Aardcure WBS is an acrylic modified emulsion used as a curing membrane on freshly poured concrete. Aardcure WBS meets AS3799 requirements and exhibits excellent durability as a concrete sealer.

Benefits

- Dries to a clear finish
- Complies with Australian Standard AS3799
- Achieves water retention of 90% or greater
- Totally water based
- Single pack
- Reduces plastic shrinkage
- Meets low VOC requirements
- Can be applied by spray, roller or brush
- Will not yellow in sunlight
- Eliminates the need for curing by ponded water, damp hessian or polythene sheeting
- Seals concrete surfaces
- Takes most after trades
- Equipment washable in water

Uses

Aardcure WBS is suitable for curing all freshly laid concrete either smooth or textured, indoors or outdoors.

Surface application

Apply Aardcure WBS to the concrete as soon as the bleed water has gone and the concrete has hardened sufficiently so as not to be marked by the application process. Apply Aardcure WBS undiluted at a rate of 1 litre per 5m².

Best applied by spray. It can also be applied by brush, roller or broom.

If after trades need to be applied it is recommended that a period of 28 days from the date of pouring has elapsed before any after trades are applied.

NOTE: Ensure all equipment is thoroughly cleaned in water.

Typical properties and application data

Appearance:	Milky white emulsion
Coverage:	5m ² per litre
Viscosity:	20 - 22 seconds (Ford #4)
Solids:	30% +/- 1%
Solubility in Water:	Totally soluble
Flash Point:	Not applicable
Solvents:	Not applicable
Shelf Life:	12 months maximum
Dry Time:	Tack Free: 30 mins
	Hard Dry: 4 hours
	Trafficable: 12 hours
Application Temperature:	10°C - 35°C
Application By:	- Spray - Brush - Roller - Broom
Packaging:	- 1000Lt Palletcons - 205 Lt Epon lined drum - 20 Lt Plastic Container
UN Number:	Not applicable
Hazchem Code:	Not applicable
Packaging Group:	Not applicable
Poison Schedule:	N/A
Dangerous Goods Class:	Not applicable

Refer to Material Safety Data Sheet for precautions and personal protection.

Disclaimer: Any advice, recommendation, information, assistance or service provided by Mirafloor in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Mirafloor to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Mirafloor is provided without liability.