



Description

Miraseal PS Enhance is a single pack, resin solution, available as an alcohol based product, giving quick surface drying, with cure taking 24-36 hours @ 25°C.

Miraseal PS Enhance contains selected ingredients, which contribute to durability, a wet-look and mar resistance resulting in an outstanding finish for polished concrete, granite, limestone, marble, slate & unglazed clay tiles.

Miraseal PS Enhance when used appropriately will give substrates oil & water repellent qualities, provides a finish that is UV resistant, and protects against efflorescence and dirt pickup.

Advantages

- Seals against Oil & Water
- Hardwearing
- Ideal for: Natural Stone
 - Concrete
 - Internal or external use

Directions for use

Ensure substrate is clean, dust, & stain free after laying procedures. Stir thoroughly (do not stir air into the coating); One to two coats of the solution should be applied to achieve an enhanced appearance. A saturation single coat or two coats of the solution should be applied to achieve an enhanced appearance with a gloss, wet-look. Remember the properties of the substrate, ie porosity, profile will greatly influence the number of coats required. Buff surface to ensure no excess of uncrosslinked material remains.

Caution: Too many coats will result in a slippery and perhaps tacky surface.

Miraseal PS Enhance can be applied with a soft, lint-free cloth, sponge, or paint brush. Excess material should be removed to prevent inconsistencies in the enhancement. The product should be fully cured within 24 hours.

A test patch should be performed prior to general application with the customer's approval to ensure the desired appearance is achieved.

For all commercial and other high traffic areas, pretesting is suggested, to ensure expected outcomes are achieved.

Coverage

On "tight surfaces" expect 5-10m²/L.

On more open surfaces 1-2m²/L. Can be applied over Miraseal Preseal.

First Aid

If poisoning occurs, contact a doctor or Poisons Information Centre Phone Australia 131126 or New Zealand 03 4747000. If swallowed, do NOT induce vomiting. Give glass of water. If skin contact occurs, remove contaminated clothing and wash skin thoroughly with plenty of soap and water. If irritation persists consult a doctor. If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

Limitations

Do not use at temperatures below 10°C as the product will not crosslink. Do not use on impervious surfaces similar to glazed porcelain, or glazed earthenware.

Clean up

Turps, Xylene or StripSeal

Storage

Keep in a cool dry place away from incompatible materials & ignition sources.

Refer to Material Safety Data Sheet for precautions and personal protection.

Disclaimer: Any advice, recommendation, information, assistance or service provided by Mirafloor in relation to goods manufactured or supplied by them or their use and application is in good faith and is believed by Mirafloor to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by Mirafloor is provided without liability.